

【init.dスクリプト作成例】

保存先：/etc/rc.d/init.d/

chmod +x スクリプト名で実行権限付与する

```
#!/bin/bash
#
# Startup script for the Apache Geronimo
#
# chkconfig: 345 80 15
# description: Geronimo is Apache's ASF-licensed J2EE server
# processname: geronimo
#
# Source function library.
if [ -f /etc/init.d/functions ] ; then
    . /etc/init.d/functions
elif [ -f /etc/rc.d/init.d/functions ] ; then
    . /etc/rc.d/init.d/functions
else
    exit 0
fi
RETVAL=0
start(){
    if [ -z $(/sbin/pidof java) ]; then
        echo "Starting geronimo"
        $GERONIMO_HOME/bin/startup.sh
        touch /var/lock/subsys/geronimo
    else
        echo "geronimo allready running"
        RETVAL=3
    fi
}
stop(){
    if [ ! -z $(/sbin/pidof java) ]; then
        echo "Shutting down geronimo"
        $GERONIMO_HOME/bin/shutdown.sh
    until [ -z $(/sbin/pidof java) ]; do ;; done
    rm -f /var/lock/subsys/geronimo
    else
        echo "geronimo not running"
        RETVAL=3
    fi
}
restart() {
    stop
    start
}

case "$1" in
    start)
        start
        ;;
    stop)
        stop
        ;;
    restart)
        stop
        start
        ;;
    status)
        if [ -f /var/lock/subsys/geronimo ]; then
            echo $"Apache Geronimo is enabled."
            RETVAL=0
        else
            echo $"Apache Geronimo is disabled."
            RETVAL=3
        fi
        ;;
    *)
        echo "Usage: $0 {start|stop|restart|status}"
        esac
    exit $RETVAL
```